

N-ST ANTI-SLIP TAPE



PRODUCT CARD

ADVANTAGES AND BENEFITS

- > Anti-slip film - reduces the risk from falling or slipping and increases the safety level
- > Easy to apply
- > Good abrasion, tearing and impact resistance
- > Easy to remove after use

TYPICAL APPLICATIONS

- > Reduces the risk of falling or slipping on slippery surfaces
- > Tape protects all kind of smooth and rougher surfaces like chipboard, wood and carpet against dust, foot prints, construction material, paint and water.
- > The product is also used to protect spray cabins and aircraft wings during repair and maintenance.

CONSTRUCTION

Backing: Embossed PP/PE film
Adhesive: Acrylic emulsion-based

COLOR(S)

White

TECHNICAL DATA

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	240	µm	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 400	cN/20mm	-
Tensile Strength	120	N/20mm	(+/- 10%)
Application Temperature Range	from +18 to +25	° C	-
	from +64 to +77	F	-
Service Temperature Range	from 15 to +40	° C	-
	from 59 to 104	F	-



The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE

Tape should be stored in its original packaging in a cool, dry area (15°C - 30°C (59°F - 86°F) and 40% - 75% relative humidity) away from direct sunlight and should be used within 6 months of date of shipment.

RECOMMENDATIONS FOR USE

Surfaces to which tape is applied should be: clean, dry and free of grease, oil, detergents and other contaminants.

Depending on the type of substrate and environment conditions, adhesive residue can appear after removing the tape.

Surface protection tapes are not meant for permanent protection, they should be removed at the end of the supply chain.

ATTENTION:

Before applying the tape, test it!

Clean removal (i.e. leaving no adhesive residue) may vary depending on the type of surface, weather conditions (temperature, sunlight, humidity) and paint used (most often the tape is stuck to a painted or primed surface).

UTILIZATION

Product Mixed waste
Packaging Marking on the packaging

PRODUCT SAFETY INFORMATION

The product is intended for professional use and may only be used within the scope of the application intended by the manufacturer, by trained persons and in accordance with the requirements of health and safety regulations specifying safe working conditions for the place of work and its type.

The product is not a construction product.

The product is not intended for children, pregnant women, people with physical or mental disabilities and people under the influence of any drugs.

The product is not a toy and must not be left unattended near places where a child has free access.

The product is flammable - as a result of the action of an open flame or high temperature, there is a risk of melting, ignition and fire.

The product should not be used to secure elements under voltage, to secure, connect or stiffen damaged, moving or stress-bearing elements.

The product cannot be reused - it is disposable.

The product complies with Regulation (EC) No. 1907/2006 REACH of the European Parliament and of the Council and does not contain SVHC substances.

