

PRODUCT CARD

**ADVANTAGES AND BENEFITS**

- > Strong
- > High resistance to extremal conditions
- > Highly durable
- > Highly efficient

**TYPICAL APPLICATIONS**

- > Bundling
- > Fixing
- > Reinforcing
- > Many more...

**CONSTRUCTION**

Overall Grade: Outside Grade  
Backing: Synthetic Cloth Laminated  
Adhesive: Synthetic rubber/Resins

**COLOR(S)**

White



**TECHNICAL DATA**

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	200	µm	(+/- 15%)
Adhesion to Stainless Steel 180°	≥ 15	N/2,5cm	-
Tensile Strength	30	N/cm	(+/- 10%)
Application Temperature Range	from +18 to +25	° C	-
	from +64 to +77	F	-
Service Temperature Range	from -5 to +60	° C	-
	from 23 to 140	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**STORAGE**

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C (70°F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment.

**RECOMMENDATIONS FOR USE**

Surfaces to which tape is applied should be: clean, dry and free of grease, oil, detergents and other contaminants.

**ATTENTION:**

Before applying the tape, test it!

**UTILIZATION**

Product                                      Mixed waste  
Packaging                                     Marking on the packaging

**PRODUCT SAFETY INFORMATION**

The product is intended for professional use and may only be used within the scope of the application intended by the manufacturer, by trained persons and in accordance with the requirements of health and safety regulations specifying safe working conditions for the place of work and its type.

The product is not a construction product.

The product is not intended for children, pregnant women, people with physical or mental disabilities and people under the influence of any drugs.

The product is not a toy and must not be left unattended near places where a child has free access.

The product is flammable - as a result of the action of an open flame or high temperature, there is a risk of melting, ignition and fire.

The product should not be used to secure elements under voltage, to secure, connect or stiffen damaged, moving or stress-bearing elements.

The product cannot be reused - it is disposable.

The product complies with Regulation (EC) No. 1907/2006 REACH of the European Parliament and of the Council and does not contain SVHC substances.

